

SECTION Four, 14,

TOWNSHIP

Elevn 111

Surveyed by J. F. Peyton Surveyor L. C., Aug. the 23rd 1854,
and corners re-set. Bearings taken &c. From No 2 to 8 inclusive
Surveyed by J. H. Davis Feb. 9th 1861 Bearings taken same as
lines.

North line of Sec 4 T 11 R 8 W

| | | | | |
|---|---|-------------------------------------|---|-------------|
| | | | | |
| | | | | |
| 2 | 8 | 7 | 6 | 5 |
| 3 | S ² E ¹ , S ²⁰ .9' | S ²⁰ S ²⁰ .9' | | |
| 4 | | | 1 | By, Peyton, |

Corner No 1 S. E corner Sand Stone marked S 25.4 S 9.8 10. {Established from original bearings

| | |
|---|---|
| " " | Beech 14 S 43 W 2 3 L " |
| " " | B. Walnut 2 S 70 E 2 7 L " |
| " 2 Sand Stone M ² /E ¹ d 1/8 S | (W) Beech 16 S 31 E 2 9 the dist. W. do. 16 N 13 W 4 9 " |
| " " | Sugar 16 N 23 W 90 " |
| " " | Original Walnut, " |
| " 4 S. Stone 1/8 S. | Ironwood 5 N 19 E 3.2 an Elm 5 S 23 W 18 " |
| " " | W. Oak 24 S 30 W 80 1/4 " |
| " 6 Sand Stone 1/8 S. | W Beech 12 S 42 W 10 1/2 " |
| " " | Beech 18 West 6 1/2 " " |
| " 7 Sand Stone 1/8 S. | do do. 16 S 42 E 4 4 " |
| " " | Sugar 6 S 18 E 22 1/2 " |
| " 8 Sand Stone 1/8 S. | an Ash 6 S 3 E 15 1/4 " |
| | Ash 6 N 41 W 7 3/2 " |
| | Beech 8 S 56 W 6 1/2 " |

John H. Davis, Surv. L. C.